

Water-Resistant 15 mil “Thrifty” Banner for Water-Based Inkjet Printers

- Scrim-reinforced vinyl designed to create cost-effective graphics
- Great for banner jobs when economy and quality is needed

Properties:

| | |
|-----------------|--|
| Product Number: | KJWPBANNER |
| Material: | Tear-resistant polyester fabric embedded between two white vinyl layer |
| Caliper/Gauge: | 15 mil |
| Weight: | 445 g/m ² |
| Opacity: | >85 |
| Brightness: | >120 |
| Gloss Level: | 2 (avg) @ 60° |

Printer/Ink Compatibility:

Encad, ColorSpan, Hewlett-Packard, Mimaki, Roland and Epson series dye & pigment-based inks Saturation level of this product is 250% and heavy coated paper setting in most RIPs is appropriate.

Ink Dry Time: Varies with type and amount of ink, relative humidity and temperature.

Environment:

| | |
|---------------------------|--|
| Printing: | 60-80° F, 50% Relative Humidity |
| Ideal Storage Conditions: | 70° F (21° C), 50% Relative Humidity, store in original packaging. |
| Handling Requirements: | Due to absorptive nature of the coating, avoid touching the coated surface with bare skin. Always wear cotton gloves when handling inkjet-coated materials. Rolls are supplied with the coated surface wound out. When rolling graphics, always roll so that the thinner material is on the outside surface of roll. |
| Life Expectancy: | Outdoor - up to 6 months without lamination. |
| Shelf Life: | 1 year from ship date when stored in proper conditions. |

Finishing/Lamination: Always use pressure sensitive laminates
Before applying laminate, allow image to dry for 24 hours.

Standard Warranty

All statements, technical information and recommendations about Kapco products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Kapco products are sold with the understanding that the Purchaser has independently determined the suitability of such product for its purposes. Kapco products are warranted to be free from defects in material and workmanship for either one year (or the period stated on the specific product information literature in effect at time of delivery, if longer) from date of shipment if said product is properly stored and applied. It is expressly agreed and understood that Kapco's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited to repair or replacement of defective product without charge at Kapco's plant or at the location of product (at Kapco's election), or in the event replacement or repairs is not commercially practical, to Kapco's issuing Purchaser a credit reasonable in light of the defect in the product.

Kapco's liability for defective products shall not exceed the purchase price paid therefore by Purchaser and in no event shall Kapco be responsible for any incidental or consequential damages whether foreseeable or not, caused by defects in such product, whether such damage occurs or is discovered before or after replacement or credit, and whether or not such damage is caused by Kapco's negligence.

No express warranties and no implied warranties, whether of merchantability or fitness for any particular use, or otherwise (except as to title) other than those expressly set forth above which are made expressly in lieu of all other warranties, shall apply to products sold by Kapco. Kapco specifically disclaims and excludes all other such warranties, no waiver, alteration, addition or modification of the foregoing conditions shall be valid unless made in writing and manually signed by an officer of Kapco.